



The Tactive TWI is an ultra-versatile kiosk thought out for interactive applications such as wayfinding, 3D map viewing and video catalogues. This is the perfect solution for shopping malls, museums, showrooms, or fairs. The landscape display has an integrated touch screen with an anti-scratch and anti-reflective 4mm glass, giving you speed and sensibility never seen before. The frontal panel can host devices such as a webcam, card reader, barcode reader or 80mm thermal printer, useful for extra income through upselling and cross-selling activities. The double back panel on the other hand allows for maintenance services in an easy and fast way.

ENVIRONMENT

Indoor IP20 (Nema 1) IP20 (Nema 1) dust proof Temperature range from 0°C to +40°C

TECHNOLOGY AND USAGE

Primary brand PRO grade LCD 24/7 usage 12 point PCAP touch screen

STRUCTURE

Robust steel structure
Ergonomic design
Safety Lock and invisible screws and hinges
Customizable frontal panel
(printers/card reader)
Easy access for maintenance

AVAILABLE SIZES

landscape



49"





Technical Specification



	TWI.L43	TWI.L49
General		
Screen orientation	Landscape	Landscape
Screen size (inch)	43"	49"
Screen active area (cm)	95 X 54	107,4 × 60,4
Display brightness (nit)	400	500
Screen resolution (pixel)	Full HD - 1920x1080	UHD - 3560x2160
Contrast ratio (typ)	4000:1 (typ)	1100:1 (typ)
Viewing angle (H/V)	178°/178°	178° / 178°
Backlight Life Cycle	50.000 hours	50.000 hours
System operation	24/7/365	24/7/365
Screen side	Single	Single
Touchescreen	PCAP 12P	PCAP 15P
Environment Environment protection	Indoor IP20 (Nema 1) / IP54 front	Indoor IP20 (Nema 1) / IP54 front
Sun exposure	not allowed	not allowed
•	0°C / +40°C	0°C / +40°C
Operating temperature	0 0 7 140 0	0 0 7 140 0
Environment humidity	10% - 80%	10% - 80%
Antivandal protection	Antivandal glass	Antivandal glass
Enclosure		
Air cooling system	passive dissipation	passive dissipation
Enclosure material	galvanized steel	galvanized steel
Glass	Scratch-free glass (3mm)	Scratch-free glass (3mm)
Glass reflection	Antireflective	Antireflective
Standard enclosure color	White (RAL9010)	White (RAL9010)
Standard glass color	Black (RAL 9005)	Black (RAL 9005)
Power		
Vac supply	230V AC +/- 10	230V AC +/- 10
Power consumption (typ)	60 W	135 W
Dimensions		
Height (cm)	120	120
Width (cm)	107	121
Depth (cm)	65	65
Weight (Kg)	135	150
Notes		

